
## NOTES: UNLESS OTHERWISE SPECIFIED

- 1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT.
- 2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.3
- 3. 100% TESTED FOR OPTICAL PERFORMANCE, END FACE CRITERIA AND CLEANLINESS.
- 4. CABLE ASSEMBLIES ARE MANUFACTURED TO C ENTERPRISES STANDARDS.
- 5. STANDARDS AND SPECIFICATIONS AVAILABLE UPON REQUEST.

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
Α	-	INITIAL RELEASE	K.T.	01/30/2017	A.J.



			ASSEMBLIES BY FIBER COLOR											
			COLOF	LOR ASSEMBLY NUMBER		BER	DESCRIPTION: SC-NOCLIP UPC POLISH / UNTERMINATED SIMPLEX FIBER SM 900 um TIGHT BUFFER							
			BLUE SUBS01SBXXXXXP <b>U</b>		XP <b>U</b>	DESCRIPTION. SO-NOCE OF OF OLIGIT/ ON TEXAMINATED SIMPLEX FIBER SIM 900 UIII TIGHT BUFFER								
			ORANGE SUBS01SBXXXXXP <b>0</b>		XP <b>O</b>	DRAWN	K. THOMAS	01/30/2017			C ENTERPRIS	SES		
			GREEN SUBS01SBXXXXXP <b>G</b>		XP <b>G</b>	BY:					2445 CADES			
			BROWN SUBS01SBXXXXXPF		XP <b>F</b>	APVD	A. JENSEN	01/30/2017	7 C.ENTERPRISES		VISTA CA 92081			
			TEST LIMITS			BY:	7 02.102.1	0 1/00/2011	_ C	necting Today's Infrastructures	760-599-5111			
BILL OF MATERIALS			AT 1310 nm			DIMENSIONS: METRIC [IMPERIAL]			TITLE:	SC/UNTERM SM	900 um SIMF	PLEX		
ITEM	QTY	COMPONENT	MAX. TYP. MIN. TYP.			TYP.	PROPRIETARY AND CONFIDENTIAL			SIZE	DWG. NO.		REV	
2	AR	SINGLEMODE OS2 900 um TIGHT BUFFER SIMPLEX FIBER; SEE TABLE FOR COLORS: PERFORMA			R.L.	R.L.	THIS DOCUMENT CONTAINS PROPRIETAL INFORMATION OF C ENTERPRISES, NOT			Α	SUBS01SBXXXXXP_		A	
1	1	SC-NOCLIP SM UPC POLISH; BLUE HOUSING, 900 um BLUE BOOT: PERFORMA		<=0.50dB		60dB	USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.			SCALE: NOT TO SCALE		SHEET 1	OF 1	