NOTES: UNLESS OTHERWISE SPECIFIED DESCRIPTION DATE CHECKED REV ECR BY 1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT. Α INITIAL RELEASE K.T. 03/30/2017 A.J. 2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.3 3. 100% TESTED FOR OPTICAL PERFORMANCE, END FACE CRITERIA AND CLEANLINESS. 4. CABLE ASSEMBLIES ARE MANUFACTURED TO C ENTERPRISES STANDARDS. 5. STANDARDS AND SPECIFICATIONS AVAILABLE UPON REQUEST. 6 HEAT SHRINK. ASSEMBLY LENGTH [24 IN] 900 um TIGHT-BUFFERED FIBER -VIEW A Ø 5.5 mm 76\ 11 VIEW A CROSS SECTION NOT TO SCALE 900 um TIGHT-BUFFERED FIBER DEPICTION OF PACKAGED ASSEMBLY ARAMID YARN FOAM PACKING BLOCK **OUTER JACKET** FLAME RETARDENT DESCRIPTION: LC UPC POLISH / UNTERM., 12 FIBER SINGLE-MODE OFNR DIST CABLE, 900 um BREAKOUT 400 FIBERS AND CONNECTORS DRAWN **C ENTERPRISES** K. THOMAS 03/30/2017 SECURED IN A FOAM BLOCK BY: 2445 CADES WAY 4000 AND BAGGED. VISTA CA 92081 APVD A. JENSEN 03/30/2017 **C**·ENTERPRISES 760-599-5111 BY: DIMENSIONS: METRIC [IMPERIAL] TITLE: SURI12LBXX9XXPX **BILL OF MATERIALS** DWG. NO. REV SIZE PRODUCT ITEM QTY PROPRIETARY AND CONFIDENTIAL SINGLE-MODE OS2 OFNR 12 FIBER DIST CABLE; YELLOW: SURI12LBXX9XXPX Α THIS DOCUMENT CONTAINS PROPRIETARY 2 AR INFORMATION OF C ENTERPRISES. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT LC-UNCLIPPED UPC POLISH; BLUE HOUSING, BLUE BOOT: SCALE: NOT TO SCALE SHEET 1 OF 1 1 12 WRITTEN PERMISSION. ALL RIGHTS RESERVED. PERFORMA