



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT.
2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-B.3
3. 100% TESTED FOR OPTICAL PERFORMANCE, END FACE CRITERIA AND CLEANLINESS.
4. CABLE ASSEMBLIES ARE MANUFACTURED TO C ENTERPRISES STANDARDS.
5. STANDARDS AND SPECIFICATIONS AVAILABLE UPON REQUEST.
6. INDIVIDUALLY BAGGED.
7. LLU: LENGTH AND UNIT OF MEASURE.

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
A	-	INITIAL RELEASE	K.T.	03/28/2016	A.J.



FIBER LEG COLOR	
1	BLUE
2	ORANGE
3	GREEN
4	BROWN
5	GREY
6	WHITE
7	RED
8	BLACK
9	YELLOW
10	PURPLE
11	ROSE
12	AQUA

BILL OF MATERIALS				LC UPC POLISH PERFORMA CONNECTOR				DRAWN BY: K. THOMAS 03/28/2017	APVD BY: A. JENSEN 03/28/2017	 C ENTERPRISES 2445 CADES WAY VISTA CA 92081 760-599-5111
ITEM	QUANTITY	COMPONENT	TEST LIMITS AT 1310 nm				DIMENSIONS: METRIC [IMPERIAL]			
2	AR	FIBER SINGLE-MODE TB DIST CABLE: PERFORMA	MAX. I.L.	TYP. I.L.	MIN. R.L.	TYP. R.L.	PROPRIETARY AND CONFIDENTIAL		SIZE A	
1	12	LC-NO CLIP UPC POLISH; BLUE HOUSING, BLUE BOOT: PERFORMA	≤0.50dB	0.20dB	≥50dB	60dB	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF C ENTERPRISES. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.		DWG. NO. SUBP12LBXXXXXPI	
								SCALE: NOT TO SCALE		REV A
										SHEET 1 OF 1